




Expansion Joint Cover Systems AND Fire & Weather Barriers


- Covers blend in with surroundings
- Restrict the spread of smoke & fire
- Accommodate building movement
- Meet recognized building codes
- Meet the highest test standards



HOW TO USE THIS QUICK REFERENCE GUIDE:



HOW TO SELECT A EXPANSION JOINT SYSTEM:



[†]Thermal, wind sway & seismic is defined as per standard ASTM E1399.


*Not every option within a series is necessarily available. Exceptions may apply. Corner options available for most systems. Larger widths may be available for some systems (contact Balco directly to inquire). Visit balcousa.com for additional details, including load performance, color options and test data.

NOTE: All information is up-to-date through 3/1/24. Balco may make additions, deletions or modifications to products and content since this date. Visit balcousa.com for the latest information.

ARCHITECTURAL SYSTEMS



- INTERIOR FLOORS -



TCVS • **Flush Wall** 2-5" [50-125mm] ±100% / Seismic TCVSE AC Corner 2-4" Accordion Acoustical Ceiling 1-3" [25-75mm] ±100% / Seismic

6GWC

Corner

1-4'

6TWC WD ● ● ◆ ★ Corner Snap-on 1-4" [25-100mm]

±50% / Seismic

WDC Corner 1-4"

ARCHITECTURAL SYSTEMS cont.



INTERIOR WALLS & CEILINGS cont. **ELASTOMERIC SEAL SERIES** FOAM SEAL

75FWVPE

Corner

1-2"

75FCA Acoustical Ceiling 75FCAC 1-2" [25-50mm] Corner ±25% 75FCACE 1-2" / Thermal Corner 1-2'



1-2" [25-50mm] ±25% / Thermal



Surface Mount Smooth 1-2" [25-50mm] ±25% / Thermal



Corner

0.5-10"

Pre-compressed Primary Seal 0.5-12" [13-300mm] ±50% / Seismic

ACOUSTICAL JOINT




BOSWA/E Acryllic (and Wax) Foam 1-6" [25-150mm] Thermal Expan./Contr.



LPRE

Corner

2"



MetaBlock® (MBF2H) 2 Hour 1-4" [25-100mm] ±50% to ±100% / Seismic



Corner ±50% to ±100% / Seismic

ΜΕΤΑΜΑΤ



FR Pre-compressed Foam (2FRBCSF-SL, 3FRBCSF-SL) 2-3 Hour 0.5-5" [12.5-125mm] ±25% to ±50% / Seismic Single & two-sided Silicone



Smoke & Water Barrier (EISB) 6-24" [150-600mm] ±50% to ±100% / Seismic







1-24" [25-600mm] ±50% to ±100% / Seismic



MetaBlock[®] (MBW2H) 2 Hour 1-4" [25-100mm] ±50% to ±100% / Seismic

MetaMat™ (MW2H) 2 Hour 3" [75mm] ±50% to ±100% / Seismic



FIRE-RATED FOAM



A CSW Industrials Company





PARTITION

CLOSURES



BARRIERS



FIRESTOPPING



NOSINGS



GRIDS





TRENCH & ACCESS COVERS

ILLUMITREADTM EGRESS

Balco, Inc. Wichita, Kansas 67219 316.945.9328 | 800.767.0082 balcousa.com

A CSW Industrials Company. Balco, the logos and other trademarks are property of Balco, Inc., its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. Balco, Inc. reserves the right to change specifications without prior notice. © Balco, Inc. All rights reserved. B50081-0324