FIRESTOP SEALANT COMPARISON GUIDE

metacaulk。 1200

The Metacaulk® 1200 sealant is an extremely flexible, fire-rated caulk and spray, ideal for a variety of through-penetration and fire-resistant joint configurations, especially in drywall. In fact, the Metacaulk® 1200 has over 250 UL Classified listings for head-of-wall (HW), bottom-of-wall (BW), floor-to-wall (FW), floor-to-floor (FF), wall-to-wall (WW), curtain wall (TRC/CW) and more. This sealant comes with unique features unlike any other, even its competition. Check out the comparison:



Sealant Properties	Metacaulk 1200	Hilti CP 606	STI SpecSeal ES
Fire rating up to 4 hr	✓		/
Water-tight and smoke barrier	✓	/	/
Flame spread of 0 - ASTM E84	✓		
Smoke Index of 0 - ASTM E84	✓	/	
STC rating up to 65	✓		
Water based (easy clean-up; no re-emulsifying once dried)	✓	✓	/
Best toolability (easily brushable, trowelable, etc.)	✓		
Flexible up to ±50% movement - ASTM E1966	✓		
Mold & Fungal Growth Rating of 0 - ASTM G21	✓	✓	/
Paintable	✓	/	/
Freeze-thaw capable	✓		
No intumescent	✓	✓	/
Widest application temperature range	✓		
Widest storage temperature range	✓		
3-Year shelf life	✓		
FBC compatible (use with CPVC)	✓		
LEED compliant	✓	✓	/
VOC <10 g/l	✓		
Available in:			
Sausage	✓	/	/
Tube	✓	/	/
5gal Pail	✓	/	/
Spray	✓	/	/
Color Options:			
Red	✓	/	/
White	/	/	



The Metacaulk® 1200 product line is unquestionably exceptional. While all brands perform well, the Metacaulk® 1200 is unrivaled in performance, versatility, price, and even an astonishing 30-Year Warranty! Find your Firestop Rep: balcousa.com/rep-finder/

Competitive performance is based on publicly available information. Accuracy should be verified by the reader.

