

# (O) (O) FIRESTOP SEALANT

30oz tubes in WHITE



## FOR DRYWALL

**Conventional** & Shaft Walls:

**HEAD-OF-WALL (HW) BOTTOM-OF-WALL (BW) FLOOR-TO-WALL (FW) WALL-TO-WALL (WW)** 

### **Smoke and Sound, Fire-rated, Highly Elastomeric, Non-sag**

- Dynamic Movement Capable
- Freeze-thaw Capable
- Three-year Shelf Life
- Safe to Handle, Install, & Dispose
- 118 UL Listings
- 30 Year Warranty





metacaulk.

### IN COMPARISON:

Sealant Properties	Metacaulk 1200	USG Firecode SS	Generic Smoke & Sound
Fire-rated listings with UL	(118 total listings)	(48 total listings)	
Cartridge volume	30oz	29oz	20oz – 29oz
CPVC compatible	<b>✓</b>		
PVC compatible	✓		
Low VOC (<10 g/l)	<b>✓</b>	<b>~</b>	<b>~</b>
LEED credits	<b>✓</b>	<b>~</b>	<b>~</b>
Shelf life	3 years	1 year	1 year – 2 years
Freeze-thaw capable	✓		
Wider recommended application temperature range	<b>✓</b> (40°F - 120°F)	(55°F - ?°F)	
Wider recommended storage teamperature range	(35°F - 120°F)	(41°F - 80°F)	
Installed warranty	30 years	1 year	3 mos – 5 years
Assembly ratings	✓	<b>✓</b>	
F and FT ratings (flame)	✓	<b>✓</b>	
T ratings (temp)	✓	<b>~</b>	
L ratings (smoke)	✓	<b>~</b>	<b>~</b>
W ratings (water); no re-emulsifying once dried	✓		
Tested to ASTM E90 (sound transmission)	✓ (STC Rating of 65)	(undisclosed)	<b>~</b>
Tested to ASTM E84 (Flame Spread 0, Smoke Index 0)	✓	<b>~</b>	<b>✓</b>
Tested to ASTM E814 (through-penetration fire rating)	✓	<b>~</b>	
Tested to ASTM E1966 (joint fire rating)	<b>✓</b>	<b>~</b>	
Tested to ASTM E1399 (cyclic joint movement); dynamic movement capable	<b>✓</b>		
Tested to ASTM E119 (time temperature curve)	<b>✓</b>	<b>~</b>	<b>~</b>
Tested to ASTM G21 (fungal growth rating)	<b>✓</b>		

metacaulk. 1200 3002 WHITE

Revit Details, BIM models, Product Data Sheets, Safety Data Sheets, and more information at <u>balco.us/mc1200</u>

\*Competitive performance is based on publicly available information. Accuracy should be verified by the reader.





MFIRECODE









