



ALL-PURPOSE FIRESTOP




ELASTOMERIC

Flexible up to
25% movement



HEAT-EXPANDING

Mimics performance of
intumescent products



ENDOTHERMIC

F-Rating and T-Rating
up to 4 hours



**3in1 SEALANT
FOR JOINTS AND
THROUGH-PENETRATIONS**

**HIGHLY VERSATILE,
HYBRID FIRESTOP**

**UL LISTINGS FOR WIDE RANGE OF
APPLICATION TYPES, INCLUDING
WOOD, CONCRETE FLOOR, AND
GYPSUM/BLOCK/CMU WALLS**

VOC COMPLIANT
($<10\text{g/l}$)
for Lead Credits

Economical
compared to other
product choices

**3-YEAR
SHELF LIFE**

**NO LIMITATIONS ON
FREEZE-THAW CYCLE**

40°F to 120°F
install temp.

**STC RATING
65**

FIELD FRIENDLY
Graphite free for
smooth tooling

CPVC Approval for
both Lubrizol (FBC)
and Spears pipes

35°F to 120°F
storage temp.

**30-YEAR
WARRANTY**

UL ratings for F, T, W,
and L applications

Wet or dry protected from
mold growth with biocides
(indoor use)

Manufactured by



Available in
red or gray

Paintable

Glycol/poison free
for safe handling,
installation, and disposal

FOR MORE INFORMATION:
[balcousa.com/product/
metacaulk-150-sealant/](https://balcousa.com/product/metacaulk-150-sealant/)



BALCO.US/MC150