

metacaulk® Blaze Foam™

INTUMESCENT FIRESTOP FOAM

QUICK AND EASY
ONE STEP
INSTALLATION

NO SHELF LIFE OR
TEMPERATURE LIMITATIONS
FOR INSTALLATION

NO MATERIAL
WASTED

NO MECHANICAL
FASTENING
REQUIRED

NO EQUIPMENT (PUMPS,
ELECTRIC OR AIR) REQUIRED
FOR INSTALLATION

Blaze Foam is an intumescent compressible foam used to firestop head of wall, wall to wall and bottom of wall joint applications both dynamic and static.

PERFORMANCE

- UL Classified system up to 2 hrs in gypsum walls tested in accordance with ASTM E1966 (UL 2079) and ASTM E90
- Up to 3 hrs: UL HW-D 0948
- Up to 3 hours in concrete/CMU joint applications
- L Rating < 1 CFM/LF
- STC Rating 64
- Up to 100% extension

For flat or fluted deck applications



BALCO.US/MCBLAZE



No hazardous ingredients

Easily replaceable

Available in 1" and 1½" wide sizes

Supplied in flexible 4' lengths

Manufactured by



A CSW Industrials Company

Balco, Inc. 2626 S Sheridan, Wichita, Kansas 67217 316.945.9328 | 800.767.0082 balcousa.com

Balco, the logos and other trademarks are property of Balco, Inc., its affiliates or its licensors and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. Balco, Inc. reserves the right to change specifications without prior notice.

©2023 Balco, Inc. All rights reserved. B50142-0623